



August 19th, 2011

DRIED PINEAPPLE

PRODUCT DESCRIPTION

VARIETY:
ORIGIN:
DESCRIPTION:

APPEARANCE:
FLAVOUR AND AROMA:
TEXTURE:
MOISTURE:
METHOD OF MANUFACTURE:

MD2
Santo Domingo, Ecuador
Pineapple rings: 3-5 mm of thickness and 6-9 cm of diameter.
Cubes or chunks: 5 to 15 mm of length and width.
1/8 Rings: 2-3 cm of length and width.
Light yellow
Pineapple
Soft and dried
7 - 12%
Dehydration, products are 100% natural, without SO₂ or preservatives.

GENERAL CONDITIONS

PACKAGE:

PRIMARY PACKING:
SECONDARY PACKING:
METHOD OF TRANSPORTATION:
WAY OF TRANSPORTATION :
CAPACITY OF THE FRUIT:
MINIMUM SHELF LIFE:
(Remaining on delivery to site)

Customer specification
Bags from 250 grs. to 5 Kgs.
In cardboard boxes of up to 20 Kgs.
Packed in polypropylene bags.
Packed in cardboard boxes.
Dry containers
By air or by sea
In one 20' container : 6 MT
9 months

NUTRITION FACTS (50 gr)

| | |
|---------------|-----------------|
| FAT | 0.00g |
| SATURATED FAT | 0.00g |
| CARBOHYDRATES | 45.00g |
| DIETARY FIBER | 2.00g |
| PROTEINS | 1.00g |
| FIBER | 2.00g |
| ENERGY(kcal) | 375.98kcal/100g |
| SODIUM | 10.00mg |

MICROBIOLOGICAL ANALYSIS

| MICROORGANISM | ACCEPTABLE B2B | METHODOLOGY | LABORATORY |
|----------------------|-----------------------|--|----------------------|
| Aerobic Count | <1000 cfu/g | 3M Petrifilm AOAC 17 th 966.23 | Internal External |
| Total Coliform | <100 cfu/g | 3M PETRIFILM AOAC 18 TH 991.14 | Internal External |
| Moulds | <100 cfu/g | 3M Petrifilm FDA-BAM, CHAPTER 18 | Internal External |
| Yeasts | <5000cfu/g | 3M Petrifilm FDA-BAM, CHAPTER 18 | Internal External |
| Salmonella spp. | Negative in 375g | AOAC 18 th 967.26 FDA-BAM, CHAPTER 5 | External |

CHEMICAL ANALYSIS

| PARAMETER | ACCEPTABLE B2B | METHODOLOGY | LABORATORY |
|------------------------|-----------------------|---|----------------------|
| Moisture (g%) | 7 - 12 | BM035 Electronic Analyzer AOAC 17 th 934.06 | Internal External |
| Solids Soluble (°Brix) | 80 - 90 | AOAC 17 th 983.17 | External |

PHYSICAL ANALYSIS

| PARAMETER | ACCEPTABLE B2B | METHODOLOGY | LABORATORY |
|------------------|-----------------------|--------------------|-------------------|
| Water activity | Aw < 0.7 | Equipment:Rotronic | Internal |